

B6

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 59-145206

(43)Date of publication of application : 20.08.1984

(51)Int.Cl.

C08F 10/02
C08F 4/02
C08F 4/64

(21)Application number : 58-019340

(71)Applicant : MITSUBISHI PETROCHEM CO
LTD

(22)Date of filing : 08.02.1983

(72)Inventor : TAKAHASHI HAJIME
KAGEYAMA YOSHITERU

(54) POLYMERIZATION OF ETHYLENE

(57)Abstract:

PURPOSE: To obtain a (co)polymer of a low melt flow index, by (co)polymerizing ethylene at a high temperature in the presence of a Ziegler catalyst of a specified composition.

CONSTITUTION: A catalyst is prepared by combining (A) a solid catalyst component containing at least titanium, magnesium, and chlorine, obtained by, for example, a method comprising mixing and grinding magnesium chloride, titanium trichloride, and an electron donor, with (B) an organoaluminum compound (e.g., diethylaluminum monochloride) and (C) a silicon compound having a Si-OR bond or a Si-OCOR bond (wherein R is a 1W10 C hydrocarbon), e.g., tetraethoxysilane. The purpose (co)polymer is obtained by polymerizing ethylene or copolymerizing ethylene with an α -olefin (e.g., propylene) at a polymerization temperature of 180°C or higher in the presence of the above produced catalyst.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of
rejection]

[Kind of final disposal of application other than
the examiner's decision of rejection or
application converted registration]

[Date of final disposal for application]